DECORATIVE HAMMERED ROOF

Pierced shade sheds decorative patterned light over shrubs or gardens.

15443 CO - Unfinished Copper, Copper

15443 OB - Olde Brick®, Brass

15443 OB12 - Same as 15443 OB. Bulk packed in 12 (unbreakable master)

15443 TZT - Textured Tannery Bronze[™], Brass

15443 VG - Verdigris, Brass

Brass or Copper (Copper will naturally patina over time)

12V S8 wedge base socket

0.4.4.144.4.0.4.5.0.4.5.0.0.0.0.0.1

24.4-W(VA) 3156K (15598 CLR) Krypton light source Power usage at 12V AC input VA MAX: 24.4-W(VA)

18.5-W(VA) 3155K (15599 CLR)

2W (18036-18038) see page 159 Compares up to 18.5W Krypton

35" of usable #18-2, SPT-1-W leads. Cable connector supplied

8" In-ground stake (Included)

15601 - Surface Mounting Flange

15607 - Surface Mounting Bracket

15843 on page 10.

U.S. Patent No. D408,573

Distance from Light 1' 2' 3' 4' 5' 6' 7' 8' 9

Footcandles 8.9 2.8 .6 .15 - - - -

WT443







Hybrid Path & Spread

Let stylish design and durable construction light the way.

Enhance The Night - www.landlight.ca