## Inspired by the popular Kichler® Ripley™ outdoor lantern, the rich tones, clean lines and sturdy construction make this path light a welcome addition to any transitional outdoor lighting design. 15800 AZT - Textured Architectural Bronze (Marine grade powder coat) 15800 BBR - Bronzed Brass Cast Aluminum, Cast Brass 3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver 3000K (-200/+125) / 80s CRI

BBR

7.25"

7.25"

Square Stem

Guaranteed not to burn out for 15 years (10 commercially)



**AZT** 

Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

High - 4 W, 5.8 VA Low - 2.5W, 4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm (High), 80 Lm (Low) 3000K = 35 Lm/W (High), 20 Lm/W (Low)

24" of useable #18-2, SPT-1W leads Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange

15607 - Surface Mounting Bracket

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8

Footcandles 23.5 11.9 4.54 1.63 0.71 0.32 0.18 0.12

WT800



**Enhance The Night - www.landlight.ca**