## LED SHEPHERD'S CROOK

Traditional flare with today's LED technology.

15807 AZT - Textured Architectural Bronze (Marine grade powder coat) 15807 BBR - Bronzed Brass

Cast Aluminum, Brass

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

High - 4 W, 5.8 VA Low - 2.5 W, 4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm (High), 80 Lm (Low)3000K = 35 Lm/W (High), 20 Lm/W (Low)

24" of useable #18-2, SPT-1W leads. Cable connector supplied

8" In-ground stake

15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket

NA

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

Footcandles 19.9 10.7 3.56 1.45 0.57 0.26 0.14 0.08

WT807





Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

commercially)

**Enhance The Night - www.landlight.ca**