

LED 8" DOME

Now in Design Pro LED, a wider path and spread light that is unobtrusive in the landscape. Coordinates with the 15811 and 15870 path and spread fixtures.

15810 AZT - Textured Architectural Bronze (Marine grade powder coat)
 15810 BBR - Bronzed Brass
 15810 BE - Beach (Marine grade powder coat)
 15810 BKT - Textured Black (Marine grade powder coat)

Cast Aluminum, Cast Brass

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA
 Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm
 3000K = 35 Lm/W

30" of useable #18-2, SPT-1W leads. Cable connector supplied

8" in-ground stake

15601 - Surface Mounting Flange
 15607 - Surface Mounting Bracket

15310 - on page 98


Subjected to Highly Accelerated Life Testing - 3rd party reliability testing
 Not for use with electronic transformers

Distance from Light	0'	1'	2'	3'	4'	5'	6'	7'	8'
Footcandles	6.47	5.50	3.82	2.20	1.44	1.07	.097	0.55	0.32



WT810

Guaranteed not to burn out for 15 years (10 commercially)



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca