LED CENTER MOUNT

Unobtrusive, center mount fixture for maximum light spread with the added benefit of LED technology. Coordinates with matching LED deck light 15765 on page 24.

15826 AZT - Textured Architectural Bronze (Marine grade powder coat)

15826 BE - Beach (Marine grade powder coat)

15826 BKT - Textured Black (Marine grade powder coat)

Cast Aluminum

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm

3000K= 35 Lm/W

50" of usable #18-2, SPT-1-W leads. Cable connector supplied

8" in-ground stake

15601 - Surface Mounting Flange

15607 - Surface Mounting Bracket

15326 - on page 96

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'

8.7 4.7 2.6 1.5 .67 .29 .10



Guaranteed not to burn out for 15 years (10 commercially)

POWERED BY DESIGN PRO LED

Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca