## LED SIDE MOUNT CAST BRASS

		E	
LED technology is combined with premium solid brass material, engineered to withstand harsh coastal conditions. Coordinates with matching LED deck light 15765 on page 24.	High/Low Setting		
15827 BBR - Bronzed Brass	CAST BRASS		
Cast Brass			
3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver			
3000K (-200/+125) / 80s CRI			
High 4 W, 5.8 VA Low 2.5 W, 4 VA Multiply fixture VA by the number of fixtures used to determine size of transformer			
9V-15V AC/DC with no loss in output due to constant current technology			
Tested to an L-70 of 40,000 hours	BBR		
3000K = 140 Lm/W (High) 3000K = 80 Lm/W (Low) 3000K= 35 Lm/W (High) 3000K= 20 Lm/W (Low)			
53" of usable #18-2, SPT-1-W leads. Cable connector supplied			
8" In-ground stake	20.5"		
15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket			
15677 CLR - Sprinkler Sheid			
NA			
Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers			
Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'	POWERE		
Footcandles 31.5 17.2 6.7 2.5 1.2 0.5 - - -   Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8'	DESIGN TECHN		
Footcandles 21.3 12 4.1 1.7 0.7 0.2	Guaranteed not		
WT827	to burn out for 15 years (10 commercially)		
	Professional-grade LED lightin	Professional-grade LED lighting and	
LandLight		system components, designed and	
Enhance The Night	engineered for optimum all-w	eather	
	performance with natural lig	hting	
	performance with naturaling	inting	

A PARS

effects, deliver professional results.

Enhance The Night - www.landlight.ca