LED FUNDAMENTALS

Basic, uncomplicated design for versatility. Use along walkways or points of interest. Heavy gauge copper makes this proven look fit in any setting.

15839 CO - Unfinished Copper 15839 TZT - Textured Tannery Bronz™e (Marine grade powder coat)

Brass or Copper (copper will naturally patina over time)

3 Integrated High Output Nichia^ LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm 3000K= 35 Lm/W

55" of useable #18-2, SPT-1W leads. Cable connector supplied


8" in-ground stake

15601 - Surface Mounting Flange 15607 - Surface Mounting Bracket

15439 - on page 94

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8' Footcandles 10.77 6.12 3.87 2.57 1.99 1.77 1.12 0.87 0.61







Guaranteed not to burn out for 15 years (10 commercially)



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca