

A cast dome sculpted with a floral band and pierced to reveal a sophisticated pattern of LED light.

15857 AZT - Textured Architectural Bronze (Marine grade powder coat)

Cast Aluminum

3 Integrated High Output Nichia® LEDs, tightly binned for color uniformity, and constant current driver

3000K (-200/+125) / 80s CRI

4 W, 5.8 VA

Multiply fixture VA by the number of fixtures used to determine size of transformer

9V-15V AC/DC with no loss in output due to constant current technology

Tested to an L-70 of 40,000 hours

3000K = 140 Lm

3000K = 35 Lm/W

30" of useable #18-2, SPT-1W leads. Cable connector supplied

8" in-ground stake

15601 - Surface Mounting Flange

15607 - Surface Mounting Bracket

15457 - on page 78

Subjected to Highly Accelerated Life Testing - 3rd party reliability testing. Not for use with electronic transformers

Distance from Light 0' 1' 2' 3' 4' 5' 6' 7' 8

Footcandles

4.55 4.08 3.23 2.26 1.57 0.47 0.41 0.29 0.25

WT857





Guaranteed not to burn out for 15 years (10 commercially)



Professional-grade LED lighting and system components, designed and engineered for optimum all-weather performance with natural lighting effects, deliver professional results.

Enhance The Night - www.landlight.ca